

EddyCus® TF map 2530HF – High Frequency Imaging Device

P_T_2530HF_20



Highlights

- ▶ Contact-free imaging
- ▶ High resolution imaging
- ▶ Fast integrity assessment and defect imaging
- ▶ Complex impedance analysis for separation of electric, dielectric and magnetic properties using EddyEva analysis software

Applications

- ▶ Composition assessments of electric, dielectric, magnetic properties
- ▶ Printing
- ▶ Impregnation
- ▶ Drying
- ▶ Curing
- ▶ Chemical reaction monitoring
- ▶ Mixing
- ▶ Sorting
- ▶ Defect analysis (anomalies, hot spots)

Device Series

- ▶ Wet thickness (μm) / weight (g/m^2)
- ▶ Drying status (%)
- ▶ Permittivity (F/m) *Beta*
- ▶ Conductivity / resistivity (mOhm cm)
- ▶ Permeability (H/m) *Beta*
- ▶ Sheet resistance (Ohm/sq)
- ▶ Electrical anisotropy (%)
- ▶ Metal thickness ($\text{nm}, \mu\text{m}$)

Materials

- ▶ Wet thin films and surfaces
- ▶ Wet components and structures
- ▶ Liquids, slurries, inks, resins, dispersions, chemicals
- ▶ Powders and particle films (cosmetics and medicines)
- ▶ Bulk materials (plastics, ceramics)
- ▶ Composites (prepregs, impregnated fibers and tapes, CFRP)
- ▶ Compounds (casting compounds)

SURAGUS GmbH
Maria-Reiche-Strasse 1
01109 Dresden
Germany

For further questions:
+49 351 32 111 520

sales@suragus.com

Visit us at:
www.suragus.com
www.suragus.com/calculator
www.suragus.com/EddyCusMap2530

Made and Engineered in Germany 



Working Principle

- ▶ EddyCus® sensors generate electromagnetic fields (EMFs) consisting of electric and magnetic fields
- ▶ EMFs change when material with electric, dielect and (ferro)magnetic properties is present
- ▶ The evaluation of the resulting field changes provides
 - ▶ information on amount / volume and its properties
 - ▶ Conductivity (eg. metals, semiconductors, graphite)
 - ▶ Permeability (eg. Co, Ni, Fe)
 - ▶ Permittivity (eg. water, solvent, polymers, chemicals)
 - ▶ The separation is done by complex impedance analysis

Data Sheet

Measurement technology	Non-contact high frequency eddy current sensor
Substrates	Foils, glass, various containers
Max. scanning area	12 inch / 300 mm x 300 mm (larger upon request)
Max. sample thickness / sensor gap	Transmittance setup: 1 – 50 mm (defined by the thickest sample) Reflectance setups: infinitive (only surface area is analyzed)
Measurement types	Wet thickness (µm) / weight (g/m²) / drying status (%) Conductivity / resistivity (mOhm cm) / permeability (H/m) Beta
Measurement range / accuracy	Depends on the measurement task and the material composition and test object volume. Please consult the SURAGUS team
Scanning pitch	1 / 2.5 / 5 / 10 / 25 mm (other upon request)
Measurement points per time (square shaped samples)	100 measurement points in 0.5 minutes 10,000 measurement points in 5 minutes 1,000,000 measurement points in 30 minutes
Device dimensions (w/h/d) / weight	31.5 x 19.1 x 33.5 inch / 799 x 486 x 850 mm / 90 kg
Further available measurements	Sheet resistance, metal thickness and anisotropy imaging

Device Control and Software

- ▶ Pre-defined measurement and product recipes (sizes, pitches, thresholds)
- ▶ Line scan, histogram and area analysis
- ▶ Black and colored image coding
- ▶ Csv & pdf export
- ▶ SPC summary and export
- ▶ 3 user levels
- ▶ Material database for parameter conversion
- ▶ Edge effect compensation
- ▶ Storage and import of data
- ▶ Export of data sets (eg. to EddyEva, MS Excel, Origin)

