

EddyCus® TF portable 1010E – Handheld Emissivity Tester

P_T_1010E_20



Highlights

- ▶ Realtime and easy to use
- ▶ Emissivity conversion
- ▶ Wireless data transfer via Bluetooth
- ▶ Data center to manage and visualize data from different portable systems
- ▶ Easy to use software

Applications

- ▶ Architectural glass (LowE)
- ▶ Automotive glass (LowE)
- ▶ Transportation glass (LowE)
- ▶ Mobile friendly glass (LowE)
- ▶ Bird friendly glass (LowE)
- ▶ Window films
- ▶ Heat treated / tempered glass

Device Series

- ▶ Emissivity
- ▶ Sheet resistance (Ohm/sq)
- ▶ Metal layer thickness (nm, μm)
- ▶ Metal substrate thickness (μm)
- ▶ Conductivity / resistivity (mOhm-cm)
- ▶ Defect and integrity assessment

Materials

- ▶ Single-Silver coatings
- ▶ Double-Silver coatings
- ▶ Triple-Silver coatings
- ▶ Quad-Silver coatings
- ▶ Other emissivity coatings

SURAGUS GmbH
Maria-Reiche-Strasse 1
01109 Dresden
Germany

For further questions:
+49 351 32 111 520

sales@suragus.com

Visit us at:
www.suragus.com
www.suragus.com/calculator
www.suragus.com/EddyCusPor1010

Made and Engineered in Germany 





Measurement technology	Eddy current sensor
Measurement mode	Realtime at constant distance / contact
Substrates	Glass, foils etc.
Substrate sizes	Flat samples > 150 mm x 150 mm (6 inch x 6 inch) Curved editions are available for several applications (windshields etc.)
Measurement spot / high sensitivity zone	40 mm diameter (1.6 inch)
Power	Lithium ion battery > 9 h
Emissivity range	0.005 – 0.2
Sheet resistance range	Additional feature, 0.3 – 30 Ohm/sq
Thickness measurement of thin films (e.g. silver)	Additional feature, 5 nm – 50 nm (in accordance with sheet resistance)
Accuracy (for planar solid surfaces, e.g. glass)	< 3%
Display	2.8 inch colored touch screen
Device dimension (w/h/d) @ weight	7 inch x 3.5 inch x 1.9 inch / 178 mm x 87 mm x 48 mm @ 340g
Interfaces	Bluetooth (optional) + data center

Device Control and Software

- ▶ Portable
- ▶ Non-destructive contact measurement
- ▶ Realtime and easy to use
- ▶ Data recording function
- ▶ Accurate and reliable
- ▶ Touch screen
- ▶ Customizable calibration
- ▶ Data aggregation in PC via Bluetooth

